

Productvoordelen

- ◆ Maximale zuighoogte 8 meter
- ◆ Geschikt voor continue gebruik
- ◆ Kwaliteitspomp voor concurrerende prijs
- ◆ Hoogwaardige materialen



Optioneel

- ◆ Flushtronic 220605000 (voor 81M – 100M – 151M)



Specificaties	Model Art. nr.	81M 279310	100M 279318	100T 279319	151M 279322	151T 279323	251M 279324	251T 279325
Vermogen	PK	0,75	1	1	1,5	1,5	2	2
Vermogen	kW	0,55	0,75	0,75	1,1	1,1	1,5	1,5
Aansluiting zuig	DN	1" bi/dr	1" bi/dr	1" bi/dr	1.½" bi/dr	1.½" bi/dr	1.½" bi/dr	1.½" bi/dr
Aansluiting pers	DN	1" bi/dr	1" bi/dr	1" bi/dr	1" bi/dr	1" bi/dr	1" bi/dr	1" bi/dr
Spanning	Volt	230	230	400	230	400	230	400
Toerental	Rpm	2800	2800	2800	2800	2800	2800	2800
Watertemp. max.	°C	35	35	35	35	35	35	35

Type	Opbrengst										
		m3/h	0,6	1,2	1,8	2,4	3,0	3,6	4,2	4,8	5,4
	ltr/min	10	20	30	40	50	60	70	80	90	100
81M	H (m)	38	34	29	25	19					
100M		46	40	35	30	26	22				
100T		46	40	35	30	26	22				
151M		58	55	52	49	45	40	30	10		
151T		58	55	52	49	45	40	30	10		
251M		60	57	55	52	49	45	43	40	38	34
251T		60	57	55	52	49	45	43	40	38	34

Hoogte in meters waterkolom = (H)